

ASB-6010A

The aluminium barrier with 6 m arm



left-hand installation:
#7641V001

right-hand installation:
#7642V001

Benefits:

- simple and fast mounting due to the "Plug & Go" principle: install, plug-in, ready!
- barrier arm can be easily shortened on site
- easily operated via integrated SOMMER radio receiver (FM 868.8 MHz)¹⁾
- the automatic obstruction detection ensures optimum protection: when it contacts an obstacle the barrier opens automatically and ensures that no vehicle is clamped
- the operating force of our barriers is certified according to EN 12445 and EN 12453
- the barrier can be manually opened and closed in any position by means of the emergency crank (e.g. in the event of a power failure)



- pluggable and service-friendly motor control with a range of setting options
- numerous connection possibilities for accessory, e.g. light barriers (photo cell), induction loops, ...
- also available at SOMMER are support posts and torque support arms²⁾
- integrated warning light with a clearly visible signal effect

TECHNICAL DATA

Temperature range	-20°C to +60°C
Barrier arm	max. 6 m
Weight	approx. 40 kg
Power supply	AC 230 V, 50/60 Hz
Motor power	80 W, DC 24 V
Permitted cycles per day	max. 350
IP class	IP44



1) also available in FM 434.42 MHz. 2) The floating support is only certified for the ASB-6010 and ASB-6010A models and a boom length of up to 5m. Please only use support posts or floating supports.

Last updated: 02/2015. Literal errors, errors and technical changes excepted.



SOMMER ANTRIEBS- UND FUNKTECHNIK GMBH | HANS-BÖCKLER-STR. 21-27 | D-73230 KIRCHHEIM/TECK
PHONE +49 (0)7021/8001-0 | FAX +49 (0)7021/8001-100 | INFO@SOMMER.EU | WWW.SOMMER.EU



SOMMERGBMH



SOMMER_GMBH